TECHNICAL DATA SHEET

READY MIXED WALLCOVERING ADHESIVE – HEAVY DUTY GRADE

Description:

Heavy Duty Grade Adhesive is a ready mixed adhesive specifically designed for hanging heavy duty Wallcoverings including fabric backed vinyls and suedes, wools, wood veneers, metallic foils and materials when natural "edge curl" is experienced.

Heavy is a dry thixotropic paste with a polyvinyl acetate emulsion base. It has strong initial grab and high final bond strength to cope with most heavy contract and water sensitive Wallcoverings. This adhesive contains an efficient fungicide to protect against mould growth and

fire retardant for critical surface spread of flame applications.

Surface Preparation:

Surfaces should be sound, dry, clean and free from damp, dust and grease. Remove old Wallcoverings and any loose or flaking paint, then wash down and allow to dry. Any cracks, holes etc should be filled and high spots sanded level. New plaster should be allowed to dry out completely. Very porous or highly alkaline surfaces require a suitable primer. Gloss painted surfaces should be keyed with sandpaper and primed with Primer Sealer and lined using this adhesive diluted to a workable consistency with clean water.

Adhesive Application:

Heavy should be applied by brush, short nap roller or finely notched spatula.

Hanging Instructions:

It is important that the Wallcovering manufacturer's hanging instructions are followed at all times. If in doubt, seek advice.

Coverage:

Approximately 5 m²/kg.

HEALTH AND SAFETY - Refer to separate sheet

Note: This is a water-based product and as such the VOC content is minimal, less than 0.4 ppm. The VOC content is derived from residual monomer in the polymer, no additional coalescing solvents are added.

This information supplied is, to the best of knowledge, true and accurate, but any recommendations or suggestions made are without guarantee since the conditions of use are beyond our control.

Other Information:

Addition of VOC information

Revision date: July 2018