

TECHNICAL DATA SHEET

READY MIXED WALLCOVERING ADHESIVE –

LIGHT GRADE

Description:

Light Grade Adhesive is a ready mixed adhesive specially formulated for hanging wallpaper and lightweight contract vinyls.

A relatively high solids, high viscosity blend of natural polymers, combining good initial tack with excellent slip characteristics allowing easy positioning of Wallcovering. Light Grade Adhesive contains an efficient fungicide to protect against mould growth and also a fire retardant for critical surface spread of flame applications. Versions without fire retardant are available on request.

Surface Preparation:

Surfaces should be sound, dry, clean and free from damp, dust and grease. Remove old Wallcoverings and any loose or flaking paint, then wash down and allow to dry. Any cracks, holes etc should be filled and high spots sanded level. New plaster should be allowed to dry out completely. Very porous or highly alkaline surfaces require a suitable primer. Gloss painted surfaces should be keyed with sandpaper and primed with Primer Sealer and lined using this adhesive.

Adhesive Application:

Light should be applied by either brush or short nap roller.

Hanging Instructions:

It is important that the Wallcovering manufacturer's hanging instructions are followed at all times. If in doubt, seek advice.

Coverage:

Approximately 6-8 m²/kg

HEALTH AND SAFETY - Refer to separate sheet

Note: This is a water-based product and as such the VOC content is minimal, less than 0.4 ppm. The VOC content is derived from residual monomer in the polymer, no additional coalescing solvents are added.

This information supplied is, to the best of knowledge, true and accurate, but any recommendations or suggestions made are without guarantee since the conditions of use are beyond our control.

Other Information:

Addition of VOC information.

Revision date: July 2018