

TECHNICAL DATA SHEET

READY MIXED WALLCOVERING ADHESIVE –

MEDIUM GRADE

Description:

Medium Grade Adhesive is a high tack, fast drying, thixotropic dry paste formulated from a blend of natural and synthetic vinyl polymers giving high final bond strengths. It contains an efficient fungicide to protect against mould growth and fire retardant for critical surface spread of flame applications.

Medium is a ready mixed adhesive specially formulated for hanging a wide variety of Wallcoverings including fibreglass Wallcoverings, silks, grasscloths, linens, wools, hessians, other textiles and medium weight fabric backed vinyls.

Surface Preparation:

Surfaces should be sound, dry, clean and free from damp, dust and grease. Remove old Wallcoverings and any loose or flaking paint, then wash down and allow to dry. Any cracks, holes etc should be filled and high spots sanded level. New plaster should be allowed to dry out completely. Very porous or highly alkaline surfaces require a suitable primer. Gloss painted surfaces should be keyed with sandpaper and primed with Primer Sealer and lined using this adhesive.

Adhesive Application:

Medium should be applied by either brush or short nap roller or finely notched spatula.

Hanging Instructions:

It is important that the Wallcovering manufacturer's hanging instructions are followed at all times. If in doubt, seek advice.

Coverage:

Approximately 5 m²/kg.

HEALTH AND SAFETY - Refer to separate sheet

Note: This is a water-based product and as such the VOC content is minimal, less than 0.4 ppm. The VOC content is derived from residual monomer in the polymer, no additional coalescing solvents are added.

This information supplied is, to the best of knowledge, true and accurate, but any recommendations or suggestions made are without guarantee since the conditions of use are beyond our control.

Other Information:

Addition of VOC information.

Revision date: July 2018