

TECHNICAL DATA SHEET

VINYL OVER VINYL ADHESIVE

Description:

- * Saves time and labour.
- * Eliminates priming.
- * Ready to use.
- * Mildew resistant.
- * Hand stir well before use.
- * Contains no mercuric preservatives.
- * Avoid freezing.
- * Use only when temperature is above 50°F

Application Instructions:

- * Existing vinyl wall surface must be dry, clean and free from grease, dirt and paste residue.

- * Be certain that existing Wallcovering is firmly attached to the wall.

- * Before proceeding with any unusual condition, consult your adhesive and Wallcovering supplier.

- * Do not dilute VINYL OVER VINYL ADHESIVE.

- * For best results, apply a thin and even coat of adhesive with a brush or a roller.

- * Remove excessive adhesive from the seams, trim and other areas with clean water before it dries.

- * Dried paste on vinyl Wallcovering surface may stain.

- * For deeply embossed vinyls, it is recommended that VINYL OVER VINYL ADHESIVE is applied to the existing vinyl and then the manufacturer's instructions are followed.

- * Coverage rate is approximately 6 – 7 m²/kg.

Cleaning:

Excess adhesive must be removed whilst still wet from the decorative face of the Wallcovering and any other contaminated surface to avoid staining. Tools and equipment should be cleaned with water immediately after use.

HEALTH AND SAFETY - Refer to separate sheet

This information supplied is, to the best of knowledge, true and accurate, but any recommendations or suggestions made are without guarantee since the conditions of use are beyond our control.

Other Information:

Revision date: July 2018